

AXIS Pendant Dome

Weatherproof your Axis Network Cameras

The AXIS Pendant Dome protects the AXIS 213 PTZ, the AXIS 214 PTZ and the AXIS 231D+/232D+ Network Dome Cameras in outdoor environments as well as indoor conditions that may be humid, cold or dusty.

The housing provides IP66-class protection from dust and water ingress. With fan-assisted heating, the housing enables the camera to operate in temperatures down to -40° F (-40° C).

The dome ships with an optically clear polycarbonate lower dome that can be replaced with a tinted version. The housing provides an internal protective passage for cables and is easy to install on ceilings and walls.



- Indoor and outdoor installation

- Operating temperature

AXIS 213 PTZ Network Camera: -40° F to 100° F

AXIS 214 PTZ Network Camera: -40° F to 100° F

AXIS 231D+/232D+ Network Dome Cameras:
-40° F to 122° F

- IP66-class protection from dust and water

- Fan-assisted heater

- Variety of mounting brackets available



AXIS Pendant Dome

Technical Data – Housing

General

- Pendant mount
- Constructed of durable engineered plastic
- UV Protected, distortion free, polycarbonate lower dome

Environment

- Indoor or outdoor installation
- IP66 Rated
- Operating temperature
 AXIS 213 PTZ Network Camera: -40° F to 100° F
 AXIS 214 PTZ Network Camera: -40° F to 100° F
 AXIS 231D+/232D+ Network Dome Cameras:
 -40° F to 122° F
- Fan-assisted Heater
 Turn on: 40° F
 Turn off: 60° F

Electrical

- Ships with two indoor power supplies
- Input voltage 110-120 60HZ VAC
- Input current Max 0.4 A
- Max Output Power 40W
- Output voltage 24 VAC
- Output current 1.6 A

Dimensions and Weight

- Product dimensions (H x W x L):
 15 x 11 x 11 inches
 (381 x 280 x 280 mm)
- Shipping dimensions (H x W x L):
 19 x 12 x 12 inches
 (483 x 305 x 305 mm)
- Unit Weight: 11 lbs (5.0 kg)
- Shipping Weight: 13 lbs (6.0 kg)

Approvals

- Safety: All included electrical components are UL approved

Available Mounts

- | | |
|-------|---|
| 22059 | Corner mount adapter (must be used with 25736) |
| 21896 | Pole mount adapter, w/ banding straps and clips (Must be used with 25736 & requires banding tool) |
| 25736 | Gooseneck Wall Mount |
| 25738 | Parapet mount |

Accessories

- | | |
|----------|-----------------------------|
| 25740 | Smoked colored lower bubble |
| 25741 | Clear lower bubble |
| 5000-001 | 24VAC Outdoor power supply |

Technical Data – mounts

To receive a fully working unit for outdoor or indoor use, please use the following guide and select one item from each column. Items in light blue boxes are optional.

1	2	3	4
AXIS 213 PTZ Network Camera 	25733 Pendant Dome Outdoor 	25736 Gooseneck Wall Mount 	21896 Pole Mount  Must be used with 25736
AXIS 214 PTZ Network Camera 	25735 Pendant Dome Indoor 	25738 Parapet Mount 	22059 Corner Mount  Must be used with 25736
AXIS 231D+/232D+ Network Dome Camera 			

www.axis.com